

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
5 August 2004 (05.08.2004)

PCT

(10) International Publication Number
WO 2004/066681 A1

(51) International Patent Classification⁷: H05B 6/02

(74) Agent: ABC-PATENT, SIVILING, ROLF CHR. B. LARSEN A.S; Postboks 6150 Etterstad, N-0602 Oslo (NO).

(21) International Application Number:
PCT/NO2003/000394

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:
26 November 2003 (26.11.2003)

(25) Filing Language: Norwegian

(26) Publication Language: English

(30) Priority Data:
2003.0401 24 January 2003 (24.01.2003) NO

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (for all designated States except US): SINTEF ENERGIFORSKNING AS [NO/NO]; Sem Sælandsvei 11, N-7465 Trondheim (NO).

Published:

- with international search report
- with amended claims and statement

[Continued on next page]

(54) Title: AN APPARATUS AND A METHOD FOR INDUCTION HEATING OF PIECES OF ELECTRICALLY CONDUCTING AND NON-MAGNETIC MATERIAL



(57) Abstract: An apparatus and a method for induction heating of pieces or blanks (10) of electrically conducting and non-magnetic material, wherein a device creates a static magnetic field (3) and a second device is arranged to cause a relative movement (4) between the piece or blank (10) and the static magnetic field (3), so that current is induced (12) in the piece or blank (10) which thereby is being heated up.

WO 2004/066681 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.